

# Bulletin



Comm. Microwave	Dehumidifier	Dishwasher
Dom. Microwave	Export Comm.	Heating Product
√ <b>Laundry Product</b>	PTAC Products	Range Product
Refrigerator/Fzr	Room Air Cond.	

**Date** June 29, 2001  
**No** ASQ-234-B  
Page 1 of 1

**Type** Parts Manual Update  
Policy Letter  
√ Service Information

**Attention** Service Managers  
√ Service and Parts Managers

**Models** ALE / ALG series dryers

**Issue** Damaged Moisture Sensor Board Assembly

**Warranty** Covered by terms of product warranty, should circuit board be replaced.

**Action** Follow the procedure below for proper installation or replacement of the moisture sensor circuit board.

 <b>WARNING</b>
To avoid risk of damaging circuit board do not bend or flex the moisture sensor circuit board.

1. Assemble moisture sensor circuit board (40084301) to plastic supports (501523). Carefully align the supports to the corner holes on the circuit board and apply pressure in the corners only when attaching supports.  
**NOTE:** Do not apply pressure across the entire circuit board.
2. Attach the moisture sensor board and supports to the control hood support panel, by aligning each plastic support with the holes on the control hood support panel. Insert each plastic support by applying pressure to the corner of the circuit board at each corner.